

Art. no: LC900P Page 1 (2) [page 73]



## **Green choice**

The new Lindec® LC900P propane ride-on trowel has a powerful 25 Hp Kohler propane engine that drives the double four-bladed rotors to a top speed of 160 rpm. Lindec® LC900P propane ride-on trowel has been designed for professional flooring contractors who will be working on large areas, but especially indoors, where the demands are high on low emissions. Propane reduces carbon monoxide, hydrocarbon and nitrogen oxide emissions by 50 % compared to gasoline, and with an added catalyst (art.no: 11087) lowered the additional 90 % of the remaining 50 % (only 5 % remains). A new era in the concrete industry and the only known propane ride-on trowel on the market.

The machine is CE certified and follows all safety requirements of machine directives according to 2006/42/EG и AFS 2008:3.







**Powerful LED lamps** 

Two forward and two rear facing - improve visibility while working in dark conditions (4 x 15W).



Main power switch

Electric main power switch protect battery from discharging and from unlawful use.



Easy change of drive belt Smart features to enable

quick and smooth chance of drive belt.



Hand trowel area

pitch Each has hight adjustable trowel hand holder.



## Service, maintenance and repair

Folding seat frame for easy access to the engine and drive shafts (the gas tanks must be removed before the seat is folded).

Basic data:	LC900P
Engine (Kohler CH730LP)	25 Hp, propane
Dimensions (L x W x H)	201 x 103 x 142 cm
Panning Path Width	2 x 94 cm
Rotors (Diameter)	94 cm, 4-bladed spider
Rpm	160 rpm
Weight	425 kg (incl. gas tanks, 2 x 26 kg + gas, 2 x 16 kg)
Water Capacity	2 x 23 lit
Accessories	
Edging kit	art. no: LC900340
Dolly wheel set	art. no: LCDW
Machine cover	art. no: 11074
Additional LED lights	art. no: LC900250
Trowel pan	art. no: 11619
Composite pan	art. no: 11664
Trowel blades	art. no: 11512
Plastic blades	art. no: 11575
Combination blades	art. no: 11562
Seat armrest	art. no: LC900842
LC Seat belt	art. no: LC900876
Extra propane tank	art. no: LC900PPT

## Standard features

- 26 Hk Kohler propane engine (CH730)
- Catalyst CH730
- Specially produced spider arms containing seals to avoid concrete and concrete water getting into the spider cross, avoiding unnecessary maintenance.
- Prop shafts for best durability and easier steering
- Flip up seat frame for easy access to engine and drive shafts
- Four adjustable LED lights with possibility to
- High speed (160 rpm) for superior finishing
- Electric main power switch
- Two adjustable hand trowel holders
- Water proof electric connectors
- Counters of engine speed and hours
- Spray system (2 x 23 lit)
- Two center lifting points, including lifting bridles
- Document box (service manual)
- Cup holder, adjustable seat
- Engine oil guard, 12V charger
- CE approved

ab lindec® endeavours to provide correct information about technical properties and handling of its products. However, while ab lindec® has no control over the way in which the products are mixed and laid, or the conditions under which they set, ab lindec® can in no way be held responsible. ab lindec® is only responsible for the quality of the products at the time of delivery.