

With AB Lindec[©]'s new applicator one can easily make big treatments in a very short time, with better results and to significantly less time and cost.

A small handy machine with large capacity with unique features. Battery operation, allows the machine to the «green choice» with no fume, emissions or cables. The operation state is estimated to about 2 hrs or to about 4000 m² per battery charging.

Lap-controlled flow pump that adjusts the consumption according to the walking speed to always provide the right amount of material consumption. By other words, the consumption are the same regardless walking speed. With a potentiometer, the material consumption are adjusted. If stop walking, or going backward the flow pump automatically stops running. With a leveler on the handle, you lift up the brush alternatively mop cloth from the floor, which also helps when you shall turn or operating in tight spaces. The machine has three different tools which can be used individually or together; sprayer, brush or sweeper cloth, everything depends on how you wants to do the treatment. The tools are between 115 and 125 cm wide, which means that for each step you take you have been treated over one square meter.







The machine can easily and quickly be folded and transported in a normal car, with the simple weight of 28 kg and with dimensions of 85 x 58 x 42 cm (folded).

Basic data:	LCLA
Battery	Status indicator
System	12 V
Flow Pump	15 lit/min
Battery 12 Ah	12 Ah (2 pcs)
Battery running time	apporx 2 hrs / 4000 m ²
Dimensions	115 x 58 x 100 cm
without tools	
Dimensions	85 x 58 x 42 cm
folded	
Weight	28 kg
only machine	
Weight sprays tool	1,5 kg
Weight brush tool	3 kg
Weight mop tool	4,2 kg
Total weight,	37 kg
including all utilities	





Simple and easy to fold, pull out the bolt and fold down handle.



Easy and smooth height adjustment to adjust the height of the spray system.



To change or remove the tool, pull out the bolt's on both sides and lift straight up simultaneously.

ab lindec® endeavours to provide correct information about technical properties and handling of its products. However, while ab lindec® has no control over the way in which the products are mixed and laid, or the conditions under which they set, ab lindec® can in no way be held responsible. ab lindec® is only responsible for the quality of the products at the time of delivery.